

Metro LITE MAX

The easy way to pay
for parking

The Metro LITE MAX is the newest member of Orikan's range of pay-by-plate and pay-by-space terminals. This terminal has been specifically designed to address the needs of North American communities and provide a seamless transition between traditional cash-and-ticket meters and the latest touch-free technologies.

FEATURES

- 8.4" colour SVGA TOUCH screen
- Choice of integrated bill acceptance with optional bill change recycler or coin payment
- Ticketless
- Top up time
- Check time remaining
- Electronic locking





SPECIFICATIONS

Cabinet	Construction material and finish	Cabinet: extruded solid aluminium and cast alloy casing Non-corrosive, powder coated finish, mild steel chassis
	Dimensions	Height: 1315 mm Width: 195 mm Depth: 235 mm
	Weight	64.5kg
Power	Batteries (standard)	2 x 9 Ah 12 V
	Solar panels supplied (standard)	56 Watts (1 x 2.5 W top solar panel, 14 W back vertical solar panel, 8.5 W front vertical solar panel & 2 x 15.5 W side vertical solar panels)
	Fuses at batteries	2 A slow blow
	Mains power (optional)	AC 110-240V to DC 12V mains adapter kit
Locking system	Cabinet and vault	Secure linear locking mechanism for cash vault Southco lock for top compartment access Abloy executive locking barrel with manual override and iButton electronic locking
Customer payment options	Card payment	Real time online, PCI-DSS, EMV, P2PE compliant platform. Supports Chip, NFC & Mag Stripe
	Bill payment	Integrated bill acceptance featuring a high-capacity stacker (up to 700 bills), engineered to reject foreign, counterfeit, and damaged banknotes. Gives change, with optional bill change recycler (up to 30 bills)
	Coin payment	Built-in wet deck rejecting foreign, counterfeit & damaged coin Integrated electronic antipin shutter Integrated motorized reject mechanism Coin Tin - Tamper proof lid, Abloy executive locks. Interchangeable universal design. 2.5 litres / 0.6 gal with electronic programmable fill limits
Screen display	Touch screen	Colour 8.4" LCD 800x600 1000Nit, 2.8mm cover lens
Display wakeup	Touch bezel and proximity sensor	Capacitive touch bar and Proximity sensor unit
Configuration options	Programmable	Standard - Pay-by-Plate & Pay-by-Space Custom application options
Receipts options	Electronic receipts	SMS, email, and QR code direct download, web download
Installation	Foundation cradle adaptor plate	4 x zinc coated bolts/washers (M16) bolted into cradle which is cast into a concrete footing
Communications and management software		EziCom, with APIs for third party integration
Wireless communications		4G dual SIM modem
Maintenance diagnostics and warnings		On-site self-testing diagnostics (standard) Remote warnings
Warranty		Standard 12 months - excluding vandalism, wilful damage, accidents, acts of God